

JBC365F3A

Bay Trail M Fanless Embedded Barebone Celeron N2930 / 2 LAN / DVI-I



Features

- Bay Trail M Fanless Embedded Barebone System
- Planned Product Lifecycle Through Q1'2019
- Intel Celeron N2930 1.83-2.16GHz SoC Quad-Core 7.5W
- Supports SO-DIMM DDR3L-1333 up to 8GB Total
- Integrated Intel Graphics, 2 * Gigabit LAN
- 1 * Internal 2.5" SATA2 3Gb/s storage bay
- 1 * Full-size mSATA/Mini-PCIE Shared
- 1 * Half-size Mini-PCIE Slot
- +9V ~ +24V DC Wide Power
- Includes Wall Mount Brackets
- OPTIONAL: VESA Mount and Din Rail Mount

Part No	<ul style="list-style-type: none"> ■ HBJC365F3A-2930-B ■ HBJC365F3AW-2930-B (includes 802.11 b/g/n WIFI card)
Processor	■ Intel Celeron N2930 SoC quad-core 1.83GHz processor, 2.16GHz Burst, 7.5W TDP / 4.5W SDP
Memory	■ 1 * 204-pin DDR3L-1333 1.35V SO-DIMM up to 8GB total memory
Expansion Slots	■ 1 * Half-size PCI Express Mini Card slot (occupied on WIFI model)
Storage	<ul style="list-style-type: none"> ■ 1 * SATA2 3Gb/s ports ■ 1 * Full-size mSATA/Mini-PCIE shared slot
Network	■ 2 * Realtek RTL8111G gigabit LAN
Other Features	■ HD Audio, ACPI S3, AHCI, Watchdog Timer 10-255 min/sec,
24V	■ 1 * USB 3.0 port, 3 * USB 2.0 ports, DVI-I port, 2 * RJ45, Line-out, Antenna holes, +9V ~ +24V DC In jack
Front Panel I/O	■ Power button, Power LED, HDD LED
BIOS	■ AMI 64MB SMT Flash ROM
Box Contents	■ 60W 12V AC Adapter, US Power Cord, Manual, Driver disk, Wall mount, DVI-to-VGA adapter
Compliance	■ CE, FCC, RoHS, ErP Ready
Temperature	■ Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
Dimensions	■ 153 x 111 x 35mm (DxWxH)
Warranty	■ 1 Year limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include memory, HDD, optical, or OS.



eMail: info@ibtpanelpc.com

Toll Free: 1(866) 590-4288

IBT Technologies inc.

Tel. (514) 832-0808 Fax. (514) 832-0128

www.ibtpanelpc.com